

**UNITED STATES PATENT APPLICATION**

**FOR**

**UNIFIED DATABASE SYSTEM TO STORE, COMBINE,  
AND MANIPULATE CLOCK RELATED DATA FOR  
GRID-BASED CLOCK DISTRIBUTION DESIGN**

**INVENTORS:**

**Ralf M. Schmitt, a citizen of Germany  
Manjunath D. Haritsa, a citizen of India**

**ASSIGNED TO:**

**Sun Microsystems, Inc., a California Corporation**

**PREPARED BY:**

**THELEN, REID, & PRIEST  
P.O. BOX 640640  
SAN JOSE, CA 95164-0640  
TELEPHONE: (408) 292-5800  
FAX: (408) 287-8040**

**Attorney Docket Number: SUN-P5405**

**Client Docket Number: P5405**

## SPECIFICATION

### TITLE OF THE INVENTION

5 UNIFIED DATABASE SYSTEM TO STORE, COMBINE,  
AND MANIPULATE CLOCK RELATED DATA FOR  
GRID-BASED CLOCK DISTRIBUTION DESIGN

### FIELD OF THE INVENTION

10 [0001] The present invention relates generally to a method for determining clock circuitry  
parameters in an integrated circuit design. More specifically, the present invention relates to  
employing clock net data to determine clock insertion delays for a microprocessor design having  
grid-based clock distribution.

### BACKGROUND OF THE INVENTION

15 [0002] Clock skew adjustment and verification is an important part of digital circuit and more  
specifically microprocessor design. A clock signal provides the timing reference for all data  
exchanges inside an integrated circuit (IC) or "chip." This clock signal is provided from a single  
clock signal generator, which can be either off- chip or on-chip, and is distributed over the entire  
chip to every circuit element that requires a timing reference, for example, a flip-flop among  
20 others. The time required for the clock signal to propagate to a particular clocked element is  
known as a clock insertion delay corresponding to that clocked element. The difference between  
the insertion delays of two elements capable of exchanging data is known as the clock skew for  
these two elements. Depending on the circumstances and relative to the two elements  
exchanging data, clock skew may either make the clock signal too early or too late. Clock skew

is classified as being one of two types known as maxtime and mintime skew. Excessive clock skew can decrease the performance and increase the size and power consumption of an IC.

[0003] Turning first to FIG. 1, a block diagram and a timing diagram exemplifying maxtime type

clock skew is shown. The block diagram shows a first flip-flop (FFA) 10, a second flip-flop (FFB) 12, and a logic device 14 connected as shown. The *Clock* signal line is shown to have a skew 16 which makes the signal to the FFB 12 early and the signal to the FFA 10 late, relatively speaking. The timing diagram shows a propagation delay time of the FFA 10,  $T_{pd\_FFA}$ , a logic delay time of the logic device 14,  $T_{pd\_Logic}$ , a setup time of the FFB 12,  $T_{setup\_FFB}$ , and a time of the skew 16,  $T_{skew}$ . A combination of these times determines the usable cycle time,  $T_{usable\_cycle}$ , from a cycle time,  $T_{cycle}$ , according to the following equation.

$$T_{usable\_cycle} = T_{cycle} - T_{skew} \geq T_{pd\_FFA} + T_{pd\_Logic} + T_{setup\_FFB} \quad (1)$$

The value of the maxtime skew  $T_{skew}$  determines the usable cycle time. The greater the clock skew the smaller the usable cycle time. Therefore, it is essential for the performance of the microprocessor to analyze the clock skew for all possible paths in the circuit and to adjust the skew to achieve maximum performance.

[0004] Turning now to FIG. 2, a block diagram and a timing diagram exemplifying mintime type

clock skew is shown. The block diagram shows FFA 10 connected to FFB 12. This time, the *Clock* signal skew 16 makes the signal to the FFA 10 early and the signal to the FFB 12 late, relatively speaking. The timing diagram shows a propagation delay time of the FFA 10,  $T_{pd\_FFA}$ , a hold time of the FFB 12,  $T_{hold\_FFB}$ , and a time of the skew 16,  $T_{skew}$ .

$$T_{pd\_FFA} \geq T_{hold\_FFB} + T_{skew} \quad (2)$$

If the natural propagation delay of the FFA 10 is insufficient to achieve the necessary hold time, then additional circuitry must be added between the FFA 10 and the FFB 12 to increase the total propagation delay. This results in more die area and power being consumed. Further, the additional circuitry will have to be added before the circuit is fabricated in order to prevent potential functional failures. This increases production costs and design times.

[0005] In both of the clock skew cases described above, an accurate analysis of the clock insertion delay for substantially every single clocked element is valuable to achieving high performance in a microprocessor design. The cost to analyze the insertion delay for a given path increases in general more than linearly with the size of the problem. Analyzing the insertion delay of a large path is generally much more computationally expensive than dividing the large path into several smaller paths and analyzing each of these smaller paths separately. The sum of all of the computational costs for each of the smaller tasks is typically only a fraction of the cost for the entire problem processed as a single task. In addition, several of the smaller paths can potentially be processed in parallel, so that the total runtime cost can be reduced even further. The analysis of all of the insertion delays in a microprocessor design is typically an extremely large computational task, which exceeds any available computational resources as a single analysis task. It can better be solved by dividing this task into a large number of independent smaller tasks.

[0006] In conventional microprocessor design, a clock distribution network is tree-based, grid-based, or a hybrid of both. The tree-based clock net has a network of branches from a synthesized clock source to each clocked element. So the one and only one path can be traced

directly to the clocked element. Each path can be analyzed separately thus making the calculation of the insertion delay relatively simple and accurate. Of course for a large number of clocked elements, these calculations will still be time consuming but the exceptionally high computational cost of simulating all of the paths simultaneously is avoided.

5

[0007] The grid-based clock net has a wire grid spanning over the entire chip, for example, at distribution level two or L2. At higher distribution levels, that is, for example, levels three through ten or L3-L10, the clock net has a pre-grid distribution net that resembles a tree. At L2, the clock drivers are shorted together by the grid to equalize arrival times. The result is that there is not one and only one path that can be traced directly to the clocked element.

Furthermore, the clock arrival time at every clocked element is influenced by the load created by other clocked elements in the neighborhood. Therefore, it is not generally possible to analyze each clocked element separately. Instead the entire grid or at least a large cluster of the grid should be analyzed together to reflect the interaction of the clocked elements on the arrival time of the clock signal on the grid. Since conventionally the computation task cannot be separated easily into sub-tasks as with the tree-based clock net above, analyzing the clock insertion delay in a grid-based design is much more difficult than in a tree-based design and requires potentially a much higher computational cost.

20 [0008] Turning now to FIG. 3, a block diagram of a grid-based clock distribution system 18 is shown. The system 18 includes a phase-locked loop (PLL) 20 and a grid-based clock net 22 having levels ten through one. Levels ten through three form a pre-grid clock net or a global net and levels two and one form a local net. Only nine rows and one level one are shown for

simplicity purposes. The exact number will depend on the circumstances. A source clock signal from a source clock (not shown) is fed to the PLL 20 which produces a synthesized clock signal which is fed down through the grid-based clock net 22 from level ten to level one to the clocked elements (not shown).

5

[0009] Turning now to FIG. 4, a schematic diagram of the grid-based clock net 22 of FIG. 3 is shown. The column made up of levels ten through six is shown above and one example row of levels five through two is shown below. Each level includes a plurality of buffers 24. The number and layout of the columns, rows, levels, and buffers will depend on the particular application. In this diagram one can see how, to an extent, the pre-grid distribution net resembles a tree.

[0010] Turning now to FIG. 5, a layout diagram of the grid-based clock distribution system 18 of FIG. 3 is shown. The system 18 is shown in a substantially idealized form. This form is rarely if ever achieved in a practical application. The non-ideal form introduces random and systematic skew components. As a result, one must verify the skew based on the actual layout. In this diagram one can see the wire grid spanning over the entire chip.

[0011] In both of the clock skew cases described above with respect to FIGs. 1 and 2, it is valuable to analyze the clock insertion delay for each element to predict the clock skew for a given data transfer path and, if necessary, improve performance by adjusting the insertion delays of the involved elements. In addition to the obvious conductor lengths, the clock insertion delay depends in part on parasitic effects such as coupling capacitances to other metal lines in the

vicinity of the clock line. Therefore, the clock skew analysis has to be done after the entire microprocessor has been designed and all of the structures are present in a manufacturable form. Because all of the structures in the vicinity of the clock distribution network that might show parasitic interaction with the clock net have to be included, the clock skew analysis is typically  
5 very costly in terms of time and computational resources. Furthermore, the clock skew analysis requires circuit simulation tools with a high degree of accuracy. Any uncertainty in the clock insertion delay results caused by the limited accuracy of the simulation tools has to be accounted for as "unknown additional clock skew," thereby limiting the analysis and the resulting system performance. Similarly, the demand for high accuracy increases the cost in terms of time and computational resources. For a standard microprocessor design, that is, one having more than  
10 ten million transistors, there comes a point when simulating the complete clock distribution net at one time with high accuracy tools becomes unmanageable with conventional means. The simulation time would be unacceptable and the tools are typically not capable of dealing with such large quantities of data with high accuracy.  
15

## BRIEF DESCRIPTION OF THE INVENTION

[0012] A method of and an apparatus for determining clock insertion delays for a microprocessor design having a grid-based clock distribution is disclosed. The method includes partitioning the complete clock net into a global clock net and a plurality of local clock nets, 5 simulating a load for each of the local clock nets, simulating the global clock net, and combining the simulations to form the complete clock net. The method may further include evaluating the combination to determine whether the results converge and storing the simulation results in a Clock Data Model. When the results do not converge, the method re-simulates at least one of the local clock nets and re-simulates the global clock net. The Clock Data Model collects, manages, 10 retrieves, and queries all of the simulation information. The method may further analyze the complete clock net to predict the clock skew for a given data transfer path for potential redesign.

10  
11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46  
47  
48  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60  
61  
62  
63  
64  
65  
66  
67  
68  
69  
70  
71  
72  
73  
74  
75  
76  
77  
78  
79  
80  
81  
82  
83  
84  
85  
86  
87  
88  
89  
90  
91  
92  
93  
94  
95  
96  
97  
98  
99  
100  
101  
102  
103  
104  
105  
106  
107  
108  
109  
110  
111  
112  
113  
114  
115  
116  
117  
118  
119  
120  
121  
122  
123  
124  
125  
126  
127  
128  
129  
130  
131  
132  
133  
134  
135  
136  
137  
138  
139  
140  
141  
142  
143  
144  
145  
146  
147  
148  
149  
150  
151  
152  
153  
154  
155  
156  
157  
158  
159  
160  
161  
162  
163  
164  
165  
166  
167  
168  
169  
170  
171  
172  
173  
174  
175  
176  
177  
178  
179  
180  
181  
182  
183  
184  
185  
186  
187  
188  
189  
190  
191  
192  
193  
194  
195  
196  
197  
198  
199  
200  
201  
202  
203  
204  
205  
206  
207  
208  
209  
210  
211  
212  
213  
214  
215  
216  
217  
218  
219  
220  
221  
222  
223  
224  
225  
226  
227  
228  
229  
230  
231  
232  
233  
234  
235  
236  
237  
238  
239  
240  
241  
242  
243  
244  
245  
246  
247  
248  
249  
250  
251  
252  
253  
254  
255  
256  
257  
258  
259  
260  
261  
262  
263  
264  
265  
266  
267  
268  
269  
270  
271  
272  
273  
274  
275  
276  
277  
278  
279  
280  
281  
282  
283  
284  
285  
286  
287  
288  
289  
290  
291  
292  
293  
294  
295  
296  
297  
298  
299  
300  
301  
302  
303  
304  
305  
306  
307  
308  
309  
310  
311  
312  
313  
314  
315  
316  
317  
318  
319  
320  
321  
322  
323  
324  
325  
326  
327  
328  
329  
330  
331  
332  
333  
334  
335  
336  
337  
338  
339  
340  
341  
342  
343  
344  
345  
346  
347  
348  
349  
350  
351  
352  
353  
354  
355  
356  
357  
358  
359  
360  
361  
362  
363  
364  
365  
366  
367  
368  
369  
370  
371  
372  
373  
374  
375  
376  
377  
378  
379  
380  
381  
382  
383  
384  
385  
386  
387  
388  
389  
390  
391  
392  
393  
394  
395  
396  
397  
398  
399  
400  
401  
402  
403  
404  
405  
406  
407  
408  
409  
410  
411  
412  
413  
414  
415  
416  
417  
418  
419  
420  
421  
422  
423  
424  
425  
426  
427  
428  
429  
430  
431  
432  
433  
434  
435  
436  
437  
438  
439  
440  
441  
442  
443  
444  
445  
446  
447  
448  
449  
450  
451  
452  
453  
454  
455  
456  
457  
458  
459  
460  
461  
462  
463  
464  
465  
466  
467  
468  
469  
470  
471  
472  
473  
474  
475  
476  
477  
478  
479  
480  
481  
482  
483  
484  
485  
486  
487  
488  
489  
490  
491  
492  
493  
494  
495  
496  
497  
498  
499  
500  
501  
502  
503  
504  
505  
506  
507  
508  
509  
510  
511  
512  
513  
514  
515  
516  
517  
518  
519  
520  
521  
522  
523  
524  
525  
526  
527  
528  
529  
530  
531  
532  
533  
534  
535  
536  
537  
538  
539  
540  
541  
542  
543  
544  
545  
546  
547  
548  
549  
550  
551  
552  
553  
554  
555  
556  
557  
558  
559  
560  
561  
562  
563  
564  
565  
566  
567  
568  
569  
570  
571  
572  
573  
574  
575  
576  
577  
578  
579  
580  
581  
582  
583  
584  
585  
586  
587  
588  
589  
590  
591  
592  
593  
594  
595  
596  
597  
598  
599  
600  
601  
602  
603  
604  
605  
606  
607  
608  
609  
610  
611  
612  
613  
614  
615  
616  
617  
618  
619  
620  
621  
622  
623  
624  
625  
626  
627  
628  
629  
630  
631  
632  
633  
634  
635  
636  
637  
638  
639  
640  
641  
642  
643  
644  
645  
646  
647  
648  
649  
650  
651  
652  
653  
654  
655  
656  
657  
658  
659  
660  
661  
662  
663  
664  
665  
666  
667  
668  
669  
670  
671  
672  
673  
674  
675  
676  
677  
678  
679  
680  
681  
682  
683  
684  
685  
686  
687  
688  
689  
690  
691  
692  
693  
694  
695  
696  
697  
698  
699  
700  
701  
702  
703  
704  
705  
706  
707  
708  
709  
710  
711  
712  
713  
714  
715  
716  
717  
718  
719  
720  
721  
722  
723  
724  
725  
726  
727  
728  
729  
730  
731  
732  
733  
734  
735  
736  
737  
738  
739  
740  
741  
742  
743  
744  
745  
746  
747  
748  
749  
750  
751  
752  
753  
754  
755  
756  
757  
758  
759  
760  
761  
762  
763  
764  
765  
766  
767  
768  
769  
770  
771  
772  
773  
774  
775  
776  
777  
778  
779  
780  
781  
782  
783  
784  
785  
786  
787  
788  
789  
790  
791  
792  
793  
794  
795  
796  
797  
798  
799  
800  
801  
802  
803  
804  
805  
806  
807  
808  
809  
810  
811  
812  
813  
814  
815  
816  
817  
818  
819  
820  
821  
822  
823  
824  
825  
826  
827  
828  
829  
830  
831  
832  
833  
834  
835  
836  
837  
838  
839  
840  
841  
842  
843  
844  
845  
846  
847  
848  
849  
850  
851  
852  
853  
854  
855  
856  
857  
858  
859  
860  
861  
862  
863  
864  
865  
866  
867  
868  
869  
870  
871  
872  
873  
874  
875  
876  
877  
878  
879  
880  
881  
882  
883  
884  
885  
886  
887  
888  
889  
890  
891  
892  
893  
894  
895  
896  
897  
898  
899  
900  
901  
902  
903  
904  
905  
906  
907  
908  
909  
910  
911  
912  
913  
914  
915  
916  
917  
918  
919  
920  
921  
922  
923  
924  
925  
926  
927  
928  
929  
930  
931  
932  
933  
934  
935  
936  
937  
938  
939  
940  
941  
942  
943  
944  
945  
946  
947  
948  
949  
950  
951  
952  
953  
954  
955  
956  
957  
958  
959  
960  
961  
962  
963  
964  
965  
966  
967  
968  
969  
970  
971  
972  
973  
974  
975  
976  
977  
978  
979  
980  
981  
982  
983  
984  
985  
986  
987  
988  
989  
990  
991  
992  
993  
994  
995  
996  
997  
998  
999  
1000  
1001  
1002  
1003  
1004  
1005  
1006  
1007  
1008  
1009  
1010  
1011  
1012  
1013  
1014  
1015  
1016  
1017  
1018  
1019  
1020  
1021  
1022  
1023  
1024  
1025  
1026  
1027  
1028  
1029  
1030  
1031  
1032  
1033  
1034  
1035  
1036  
1037  
1038  
1039  
1040  
1041  
1042  
1043  
1044  
1045  
1046  
1047  
1048  
1049  
1050  
1051  
1052  
1053  
1054  
1055  
1056  
1057  
1058  
1059  
1060  
1061  
1062  
1063  
1064  
1065  
1066  
1067  
1068  
1069  
1070  
1071  
1072  
1073  
1074  
1075  
1076  
1077  
1078  
1079  
1080  
1081  
1082  
1083  
1084  
1085  
1086  
1087  
1088  
1089  
1090  
1091  
1092  
1093  
1094  
1095  
1096  
1097  
1098  
1099  
1100  
1101  
1102  
1103  
1104  
1105  
1106  
1107  
1108  
1109  
1110  
1111  
1112  
1113  
1114  
1115  
1116  
1117  
1118  
1119  
1120  
1121  
1122  
1123  
1124  
1125  
1126  
1127  
1128  
1129  
1130  
1131  
1132  
1133  
1134  
1135  
1136  
1137  
1138  
1139  
1140  
1141  
1142  
1143  
1144  
1145  
1146  
1147  
1148  
1149  
1150  
1151  
1152  
1153  
1154  
1155  
1156  
1157  
1158  
1159  
1160  
1161  
1162  
1163  
1164  
1165  
1166  
1167  
1168  
1169  
1170  
1171  
1172  
1173  
1174  
1175  
1176  
1177  
1178  
1179  
1180  
1181  
1182  
1183  
1184  
1185  
1186  
1187  
1188  
1189  
1190  
1191  
1192  
1193  
1194  
1195  
1196  
1197  
1198  
1199  
1200  
1201  
1202  
1203  
1204  
1205  
1206  
1207  
1208  
1209  
1210  
1211  
1212  
1213  
1214  
1215  
1216  
1217  
1218  
1219  
1220  
1221  
1222  
1223  
1224  
1225  
1226  
1227  
1228  
1229  
1230  
1231  
1232  
1233  
1234  
1235  
1236  
1237  
1238  
1239  
1240  
1241  
1242  
1243  
1244  
1245  
1246  
1247  
1248  
1249  
1250  
1251  
1252  
1253  
1254  
1255  
1256  
1257  
1258  
1259  
1260  
1261  
1262  
1263  
1264  
1265  
1266  
1267  
1268  
1269  
1270  
1271  
1272  
1273  
1274  
1275  
1276  
1277  
1278  
1279  
1280  
1281  
1282  
1283  
1284  
1285  
1286  
1287  
1288  
1289  
1290  
1291  
1292  
1293  
1294  
1295  
1296  
1297  
1298  
1299  
1300  
1301  
1302  
1303  
1304  
1305  
1306  
1307  
1308  
1309  
1310  
1311  
1312  
1313  
1314  
1315  
1316  
1317  
1318  
1319  
1320  
1321  
1322  
1323  
1324  
1325  
1326  
1327  
1328  
1329  
1330  
1331  
1332  
1333  
1334  
1335  
1336  
1337  
1338  
1339  
1340  
1341  
1342  
1343  
1344  
1345  
1346  
1347  
1348  
1349  
1350  
1351  
1352  
1353  
1354  
1355  
1356  
1357  
1358  
1359  
1360  
1361  
1362  
1363  
1364  
1365  
1366  
1367  
1368  
1369  
1370  
1371  
1372  
1373  
1374  
1375  
1376  
1377  
1378  
1379  
1380  
1381  
1382  
1383  
1384  
1385  
1386  
1387  
1388  
1389  
1390  
1391  
1392  
1393  
1394  
1395  
1396  
1397  
1398  
1399  
1400  
1401  
1402  
1403  
1404  
1405  
1406  
1407  
1408  
1409  
1410  
1411  
1412  
1413  
1414  
1415  
1416  
1417  
1418  
1419  
1420  
1421  
1422  
1423  
1424  
1425  
1426  
1427  
1428  
1429  
1430  
1431  
1432  
1433  
1434  
1435  
1436  
1437  
1438  
1439  
1440  
1441  
1442  
1443  
1444  
1445  
1446  
1447  
1448  
1449  
1450  
1451  
1452  
1453  
1454  
1455  
1456  
1457  
1458  
1459  
1460  
1461  
1462  
1463  
1464  
1465  
1466  
1467  
1468  
1469  
1470  
1471  
1472  
1473  
1474  
1475  
1476  
1477  
1478  
1479  
1480  
1481  
1482  
1483  
1484  
1485  
1486  
1487  
1488  
1489  
1490  
1491  
1492  
1493  
1494  
1495  
1496  
1497  
1498  
1499  
1500  
1501  
1502  
1503  
1504  
1505  
1506  
1507  
1508  
1509  
1510  
1511  
1512  
1513  
1514  
1515  
1516  
1517  
1518  
1519  
1520  
1521  
1522  
1523  
1524  
1525  
1526  
1527  
1528  
1529  
1530  
1531  
1532  
1533  
1534  
1535  
1536  
1537  
1538  
1539  
1540  
1541  
1542  
1543  
1544  
1545  
1546  
1547  
1548  
1549  
1550  
1551  
1552  
1553  
1554  
1555  
1556  
1557  
1558  
1559  
1560  
1561  
1562  
1563  
1564  
1565  
1566  
1567  
1568  
1569  
1570  
1571  
1572  
1573  
1574  
1575  
1576  
1577  
1578  
1579  
1580  
1581  
1582  
1583  
1584  
1585  
1586  
1587  
1588  
1589  
1590  
1591  
1592  
1593  
1594  
1595  
1596  
1597  
1598  
1599  
1600  
1601  
1602  
1603  
1604  
1605  
1606  
1607  
1608  
1609  
1610  
1611  
1612  
1613  
1614  
1615  
1616  
1617  
1618  
1619  
1620  
1621  
1622  
1623  
1624  
1625  
1626  
1627  
1628  
1629  
1630  
1631  
1632  
1633  
1634  
1635  
1636  
1637  
1638  
1639  
1640  
1641  
1642  
1643  
1644  
1645  
1646  
1647  
1648  
1649  
1650  
1651  
1652  
1653  
1654  
1655  
1656  
1657  
1658  
1659  
1660  
1661  
1662  
1663  
1664  
1665  
1666  
1667  
1668  
1669  
1670  
1671  
1672  
1673  
1674  
1675  
1676  
1677  
1678  
1679  
1680  
1681  
1682  
1683  
1684  
1685  
1686  
1687  
1688  
1689  
1690  
1691  
1692  
1693  
1694  
1695  
1696  
1697  
1698  
1699  
1700  
1701  
1702  
1703  
1704  
1705  
1706  
1707  
1708  
1709  
1710  
1711  
1712  
1713  
1714  
1715  
1716  
1717  
1718  
1719  
1720  
1721  
1722  
1723  
1724  
1725  
1726  
1727  
1728  
1729  
1730  
1731  
1732  
1733  
1734  
1735  
1736  
1737  
1738  
1739  
1740  
1741  
1742  
1743  
1744  
1745  
1746  
1747  
1748  
1749  
1750  
1751  
1752  
1753  
1754  
1755  
1756  
1757  
1758  
1759  
1760  
1761  
1762  
1763  
1764  
1765  
1766  
1767  
1768  
1769  
1770  
1771  
1772  
1773  
1774  
1775  
1776  
1777  
1778  
1779  
1780  
1781  
1782  
1783  
1784  
1785  
1786  
1787  
1788  
1789  
1790  
1791  
1792  
1793  
1794  
1795  
1796  
1797  
1798  
1799  
1800  
1801  
1802  
1803  
1804  
1805  
1806  
1807  
1808  
1809  
1810  
1811  
1812  
1813  
1814  
1815  
1816  
1817  
1818  
1819  
1820  
1821  
1822  
1823  
1824  
1825  
1826  
1827  
1828  
1829  
1830  
1831  
1832  
1833  
1834  
1835  
1836  
1837  
1838  
1839  
1840  
1841  
1842  
1843  
1844  
1845  
1846  
1847  
1848  
1849  
1850  
1851  
1852  
1853  
1854  
1855  
1856  
1857  
1858  
1859  
1860  
1861  
1862  
1863  
1864  
1865  
1866  
1867  
1868  
1869  
1870  
1871  
1872  
1873  
1874  
1875  
1876  
1877  
1878  
1879  
1880  
1881  
1882  
1883  
1884  
1885  
1886  
1887  
1888  
1889  
1890  
1891  
1892  
1893  
1894  
1895  
1896  
1897  
1898  
1899  
1900  
1901  
1902  
1903  
1904  
1905  
1906  
1907  
1908  
1909  
1910  
1911  
1912  
1913  
1914  
1915  
1916  
1917  
1918  
1919  
1920  
1921  
1922  
1923  
1924  
1925  
1926  
1927  
1928  
1929  
1930  
1931  
1932  
1933  
1934  
1935  
1936  
1937  
1938  
1939  
1940  
1941  
1942  
1943  
1944  
1945  
1946  
1947  
1948  
1949  
1950  
1951  
1952  
1953  
1954  
1955  
1956  
1957  
1958  
1959  
1960  
1961  
1962  
1963  
1964  
1965  
1966  
1967  
1968  
1969  
1970  
1971  
1972  
1973  
1974  
1975  
1976  
1977  
1978  
1979  
1980  
1981  
1982  
1983  
1984  
1985  
1986  
1987  
1988  
1989  
1990  
1991  
1992  
1993  
1994  
1995  
1996  
1997  
1998  
1999  
2000  
2001  
2002  
2003  
2004  
2005  
2006  
2007  
2008  
2009  
2010  
2011  
2012  
2013  
2014  
2015  
2016  
2017  
2018  
2019  
2020  
2021  
2022  
2023  
2024  
2025  
2026  
2027  
2028  
2029  
2030  
2031  
2032  
2033  
2034  
2035  
2036  
2037  
2038  
2039  
2040  
2041  
2042  
2043  
2044  
2045  
2046  
2047  
2048  
2049  
2050  
2051  
2052  
2053  
2054  
2055  
2056  
2057  
2058  
2059  
2060  
2061  
2062  
2063  
2064  
2065  
2066  
2067  
2068  
2069  
2070  
2071  
2072  
2073  
2074  
2075  
2076  
2077  
2078  
2079  
2080  
2081  
2082  
2083  
2084  
2085  
2086  
2087  
2088  
2089  
2090  
2091  
2092  
2093  
2094  
2095  
2096  
2097  
2098  
2099  
2100  
2101  
2102  
2103  
2104  
2105  
2106  
2107  
2108  
2109  
2110  
2111  
2112  
2113  
2114  
2115  
2116  
2117  
2118  
2119  
2120  
2121  
2122  
2123  
2124  
2125  
2126  
2127  
2128  
2129  
2130  
2131  
2132  
2133  
2134  
2135  
2136  
2137  
2138  
2139  
2140  
2141  
2142  
2143  
2144  
2145  
2146  
2147  
2148  
2149  
2150  
2151  
2152  
2153  
2154  
2155  
2156  
2157  
2158  
2159  
2160  
2161  
2162  
2163  
2164  
2165  
2166  
2167  
2168  
2169  
2170  
2171  
2172  
2173  
2174  
2175  
2176  
2177  
2178  
2179  
2180  
2181  
2182  
2183  
2184  
2185  
2186  
2187  
2188  
2189  
2190  
2191  
2192  
2193  
219



## BRIEF DESCRIPTION OF THE DRAWINGS

[0013] The accompanying drawings, which are incorporated into and constitute a part of this specification, illustrate one or more embodiments of the present invention and, together with the detailed description, serve to explain the principles and implementations of the invention.

5

In the drawings:

FIG. 1 is a block diagram and a timing diagram exemplifying maxtime type clock skew;

FIG. 2 is a block diagram and a timing diagram exemplifying mintime type clock skew;

FIG. 3 is a block diagram of a grid-based clock distribution system;

FIG. 4 is a schematic diagram of the grid-based clock net of FIG. 3;

FIG. 5 is a layout diagram of the grid-based clock distribution system of FIG. 3;

FIG. 6 is a logic flow diagram of a method of determining clock insertion delays for a microprocessor design having grid-based clock distribution;

FIG. 7 is a logic flow diagram of the simulation of each of the plurality of local clock nets; and

FIG. 8 is a logic flow diagram of the simulation of the global clock net.

## DETAILED DESCRIPTION

[0014] Embodiments of the present invention are described herein in the context of a unified database system to store, combine, and manipulate clock related data for a grid-based clock distribution design. Those of ordinary skill in the art will realize that the following detailed description of the present invention is illustrative only and is not intended to be in any way limiting. Other embodiments of the present invention will readily suggest themselves to such skilled persons having the benefit of this disclosure. Reference will now be made in detail to implementations of the present invention as illustrated in the accompanying drawings. The same reference indicators will be used throughout the drawings and the following detailed description to refer to the same or like parts.

[0015] In the interest of clarity, not all of the routine features of the implementations described herein are shown and described. It will, of course, be appreciated that in the development of any such actual implementation, numerous implementation-specific decisions must be made in order to achieve the specific goals of the developer, such as compliance with application- and business-related constraints, and that these specific goals will vary from one implementation to another and from one developer to another. Moreover, it will be appreciated that such a development effort might be complex and time-consuming, but would nevertheless be a routine undertaking of engineering for those of ordinary skill in the art having the benefit of this disclosure.

[0016] In accordance with the present invention, the components, process steps, and/or data structures may be implemented using various types of operating systems, computing platforms,

computer programs, and/or general purpose machines without departing from the scope and spirit of the inventive concepts disclosed herein.

[0017] Turning now to FIG. 6, a logic flow diagram of a method of determining clock insertion

5 delays for a microprocessor design having grid-based clock distribution is shown. The method uses as an input a database containing the entire network information for the microprocessor.

This includes the complete clock net information. Typically, the method extracts each piece of information from this database only once but this may not necessarily be the case. The process

begins at START. At block 30, the process partitions the complete clock net into a global clock

10 net and a plurality of local clock nets. The global clock net includes levels ten through three and those portions of level two that are outside of all of the plurality of local clock nets. Each of the

plurality of local clock nets includes portions of level two and level one. The location of the local clock nets can be determined in any of a number of ways. One valid approach is to break

15 the complete clock net into a plurality of parts approximating rectangular grid coordinates. The designation of the global clock net may be thought of as horizontal partitioning. The designation

of local clock nets may be thought of as vertical partitioning. It may be desired or required to break one or more of the local clock nets down even further. This would result in sub-, sub-sub-,

etc. local clock nets. At block 32, the process simulates each of the plurality of local clock nets. The process will be described in more detail below. If sub-local clock nets were created in block

20 30, then the lowest sub-local clock net is simulated first and then each successively higher sub-

local clock net is simulated until the highest local clock net has been simulated. In those instances when the simulations of the local clock nets do not depend on one another, they may be

processed in parallel. The result is a load for each of the local clock nets on the global clock net.

This load may take many forms. One valid form is that of a single capacitor for each of the connections of the local clock net to the global clock net. At block 34, the process simulates the global clock net based in part on the simulated load of each of the plurality of local clock nets.

This will also be described in more detail below. At block 36, the process combines the

5 simulations to form the complete clock net. At decision block 37, the complete clock net is evaluated to determine if the results converge. It is possible, if somewhat unlikely, that this block could be eliminated. Often, the results of the first pass will not converge as one would prefer and blocks 32 through 37 will be repeated at least once if not more. More details of this iteration aspect of the method will be described below.

10  
15  
20  
[0018] A data model that will be referred to as the Clock Data Model (CDM) collects, manages, retrieves, and queries all of the information created during the different simulations in the process. For each point where a clocked element is connected to the local clock net and where the local clock net is connected to the global clock net, an array of information is stored. First, there is the location of the point. Second, if the point has a simulated load, there is the value of the load. Third, if the point has a clocked element attached to it, there is the name of that element. Fourth, there is the clock arrival time and slope for each point. Depending on the need or desire, other information may also be included. The CDM provides a quick retrieval mechanism for clock skew and edge rate information. This mechanism can be interfaced with a  
20 timing tool to provide accurate clock arrival times for each clocked element in the microprocessor design.

[0019] Turning now to FIG. 7, a logic flow diagram of the simulation of each of the plurality of local clock nets is shown. Note that this diagram is related to block 32 of FIG. 6 above. Recall that the various local clock net simulations may be run in parallel. The process begins at START. At block 38, the process extracts the layout of the local clock net from the microprocessor network database. In order to account for all of the coupling capacitances, the conductors routed above and through the local clock net are also extracted. One can visualize this as though a vertical cross section has been taken of the circuit delineated by the local clock net. This serves to further emphasize the use of the term vertical partitioning. The clock distribution is traced by starting at the point or points where the local clock net is connected to the global clock net. At block 40, the process extracts the component values of the elements of the local clock net from the microprocessor network database. At block 42, the process simulates the local clock net based on the layout and the component values. At least initially, it may be assumed for simulation purposes that the clock arrival times from the global clock net will be simultaneous at all points where the local clock net is connected to the global clock net. This assumption is substantially accurate as this is the goal of the clock net designer. At block 44, the process extracts the load of the local clock net on the global clock net. In addition, the clock arrival time at each of the clocked elements can be measured. All of this information is added to the CDM.

[0020] Turning now to FIG. 8, a logic flow diagram of the simulation of the global clock net is shown. Note that this diagram is related to block 34 of FIG. 6 above. The process begins at START. At block 46, the process extracts the layout of the global clock net from the microprocessor network database. At block 48, the process extracts the component values of the

elements of the global clock net from the microprocessor network database. At block 50, the process inserts the simulated loads of the plurality of local clock nets. At block 52, the process simulates the global clock net based on the layout, the component values, and the simulated local clock net loads. The result is the clock skew distribution on the global clock net. This includes the clock skew times for all points where the local clock net is connected to the global clock net. All of this information is also added to the CDM.

[0021] Returning to FIG. 6, taken together, blocks 32-36 and the blocks of FIGs. 7 and 8 result in the initial set up of the CDM. Recall that in FIG. 7 each of the plurality of local clock nets was simulated under the assumption that the clock arrival times from the global clock net would be simultaneous at all points where the local clock net is connected to the global clock net. Recall further that these times were subsequently calculated in block 34 and FIG. 8. As a result, the assumed clock arrival value and the actual clock arrival value can be compared in block 37. If the values have not converged, then blocks 32-37 can be repeated using the calculated times rather than the assumed simultaneous times in block 42 of FIG. 7. Such an iteration will improve the accuracy of the simulations. Although the entirety of blocks 32-37 and the corresponding blocks of FIGs. 7 and 8 may be repeated, this may be undesirable and unnecessary. A more streamlined approach would be to assess each of the plurality of local clock nets in a top down manner to determine whether to re-run the simulation for each particular local clock net. Similar to above, the simulations may be re-run in parallel. All of the local clock nets are reviewed and re-run in block 32 before the global clock net is re-run in block 34. It may not be necessary to re-run the global clock net simulation if the re-calculated loads of the local clock nets attached directly to the global clock net have not changed substantially, that is, they have not

changed enough to affect the clock arrival times of the global clock net. As the various simulations are re-run, the CDM is updated. In an effort to further streamline the iteration process, it is possible to skip blocks 38 and 40 of FIG. 7 as this information is already stored in the CDM and has not changed. Also, it is possible to skip blocks 46 and 48 of FIG. 8 for the same reason. Eventually through the iteration process the results will converge and the process will end leaving a substantially fully developed simulation and CDM.

[0022] With the complete clock net simulated, it is now possible to analyze the clock insertion delay for each element to predict the clock skew for a given data transfer path and, if necessary, improve performance by adjusting the insertion delays of the involved elements. If there are any performance adjustments or redesigns made, then blocks 32-37 will have to be repeated as with the iteration aspect described above. It is possible to re-run all of the simulations, but this too may be undesirable and unnecessary. A more streamlined approach would be to start by re-running the local clock net or nets involved in the redesign first. Then one can evaluate how far the ripples of the change, if any, may propagate. One may choose to compromise on the redesign to avoid sending any ripples at all. If the redesigned local clock net is connected to one or more sub-local clock nets, then the clock arrival times are evaluated to determine whether the sub-local clock net should be re-run as well. Further, the redesigned local clock net load is evaluated to determine whether the next higher clock net, either local or global, should be re-run as well. The clock arrival times and loads of each re-run clock net attached to the redesigned local clock net are also evaluated for their potential affect on their neighboring clock nets, if any. As the various simulations are re-run, the CDM is updated. Eventually the ripples will cease leaving a substantially fully developed simulation and CDM of the redesign. The redesign

process may repeat as desired or required to tailor performance adjustments or to mitigate the affects of performance adjustments.

[0023] While embodiments and applications of this invention have been shown and described, it  
5 would be apparent to those skilled in the art having the benefit of this disclosure that many more  
modifications than mentioned above are possible without departing from the inventive concepts  
herein. The invention, therefore, is not to be restricted except in the spirit of the appended  
claims.

Approved for release